

AD-A198 577

DTIC FILE COPY

(2)

NPS 68-88-008

NAVAL POSTGRADUATE SCHOOL

Monterey, California

DTIC
ELECTED
AUG 02 1988
S D
CKD



BOTTOM MOORED CURRENT METER
DATA FROM THE SOUTHEAST
HANCOCK SEAMOUNT IN APRIL 1987

Shannon C. Raugust, Russell E. Brainard
and Roland W. Garwood, Jr.

June 1988

Data Report for Period
12 April 1987 - 27 April 1987

Approved for public release; distribution is unlimited.

Prepared for:
Office of Naval Research
Ocean Sciences and Technology Division, Code 422PO
Arlington, VA 22217

NAVAL POSTGRADUATE SCHOOL
Monterey, California

Rear Admiral R. C. Austin
Superintendent

Kneale T. Marshall
Acting Provost

This work was prepared in conjunction with research sponsored by the Office of Naval Research, Ocean Sciences and Technology Division, Code 422PO, Arlington, Virginia, 22217 and funded by the Naval Postgraduate School.

Reproduction of all or part of this report is authorized.

This report was prepared by:

Shannon Raugust
SHANNON C. RAUGUST
Oceanographer

Russell E. Brainard
RUSSELL E. BRAINARD
LTJG, NOAA

Roland W. Garwood Jr.
ROLAND W. GARWOOD, JR.
Professor of Oceanography

Reviewed by:

Edward B. Thompson
CURTIS A. COLLINS
Chairman
Department of Oceanography

Released by:

Gordon E. Schaefer
GORDON E. SCHAEFER
Dean of Science and Engineering

REPORT DOCUMENTATION PAGE

1a. REPORT SECURITY CLASSIFICATION Unclassified		1b. RESTRICTIVE MARKINGS			
2a. SECURITY CLASSIFICATION AUTHORITY		3. DISTRIBUTION/AVAILABILITY OF REPORT Approved for public release; distribution unlimited			
2b. DECLASSIFICATION/DOWNGRADING SCHEDULE					
4 PERFORMING ORGANIZATION REPORT NUMBER(S) NPS 68-88-008		5 MONITORING ORGANIZATION REPORT NUMBER(S)			
6a. NAME OF PERFORMING ORGANIZATION Naval Postgraduate School	6b OFFICE SYMBOL <i>(If applicable)</i> 68	7a. NAME OF MONITORING ORGANIZATION Office of Naval Research			
6c. ADDRESS (City, State, and ZIP Code) Monterey, CA 93943-5000		7b. ADDRESS (City, State, and ZIP Code) Ocean Sciences and Technology Division Code 422PO Arlington, VA 22217			
8a. NAME OF FUNDING / SPONSORING ORGANIZATION Naval Postgraduate School	8b OFFICE SYMBOL <i>(If applicable)</i>	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER O&MN, Direct funding			
8c. ADDRESS (City, State, and ZIP Code) Monterey, CA 93943-5000		10. SOURCE OF FUNDING NUMBERS			
		PROGRAM ELEMENT NO.	PROJECT NO.	TASK NO.	WORK UNIT ACCESSION NO.
11. TITLE (Include Security Classification) BOTTOM MOORED CURRENT METER DATA FROM THE SOUTHEAST HANCOCK SEAMOUNT IN APRIL 1987					
12. PERSONAL AUTHOR(S) Shannon C. Raugust, Russell E. Brainard, and Roland W. Garwood, Jr.					
13a. TYPE OF REPORT Data	13b TIME COVERED FROM 4/12/87 TO 4/27/87	14 DATE OF REPORT (Year, Month, Day) June 1988	15 PAGE COUNT 84		
16. SUPPLEMENTARY NOTATION					
17. COSATI CODES		18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number) Southeast Hancock Seamount NOAA Ship Townsend Cromwell Bottom Moored Current Meter Ocean Planetary Boundary Layer			
FIELD	GROUP	SUB-GROUP			
19. ABSTRACT (Continue on reverse if necessary and identify by block number) Two bottom moored current meter arrays were deployed on the Southeast Hancock Seamount (29° 48'N, 179° 04'E) in April 1987. Presented in this report are velocity and temperature data collected from the current meters during this deployment.					
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT <input checked="" type="checkbox"/> UNCLASSIFIED/UNLIMITED <input type="checkbox"/> SAME AS RPT <input type="checkbox"/> DTIC USERS			21. ABSTRACT SECURITY CLASSIFICATION UNCLASSIFIED		
22a. NAME OF RESPONSIBLE INDIVIDUAL Shannon C. Raugust			22b. TELEPHONE (Include Area Code) (408) 646-3226	22c. OFFICE SYMBOL Code 68Rs	

Acknowledgements

Initial funding for this work was provided by the Office of Naval Research for the project "Studies of the Oceanic Planetary Boundary Layer" at the Naval Postgraduate School. Further data processing support was provided by the Naval Postgraduate School under the sponsorship of the Office of Naval Research project "Seamounts and Bottom Friction-Induced Topographic Scale Circulation and Mixing." Assistance and ship time was provided by Dr. George Boehlert and Mr. Chris Wilson of the Honolulu Laboratory, National Marine Fisheries Service. We thank Dr. Don Hansen of the Atlantic Oceanographic and Meteorological Laboratory for contributing current meters. Dr. Jim Schumacher, Mr. Tom Jackson, Mr. Bill Parker, Mr. Peter Proctor and other personnel at the Pacific Marine Environmental Laboratory contributed their advice and support which we gratefully acknowledge. Final graphics and calculations were done at the W. R. Church Computer Center, Naval Postgraduate School.

Accession For	
NTIS	CRA&I <input checked="" type="checkbox"/>
DTIC	TAB <input type="checkbox"/>
Unpublished <input type="checkbox"/>	
Justification	
By	
Dist. to Dept.	
Availability Status	
Dist	Approved by Special
A-1	



Table of Contents

1. Introduction	1
2. Field Program	2
3. Data Editing	6
4. Hourly Time Series	42
5. Low Pass Filtered Time Series	52
6. Low Pass Filtered Mooring Composites	62
7. Variance Density Spectra	70

List of Illustrations

Figure 1.	Location of the South East Hancock Seamount.	3
Figure 2.	Deployment configuration of moorings 87V1 and 87V2.	4
Figure 3.	Figures 3.1 - 3.24: Histograms of the velocity components and temperature of the basic 5 minute interval data set. Figures 3.25 - 3.32: Time series of the same data.	9
Figure 4.	Figures 4.1 - 4.8: Hourly vector averaged time series of the velocity components and temperature.	43
Figure 5.	Figures 5.1 - 5.8: Time series of the low pass filtered velocity components and temperature.	53
Figure 6.	Figures 6.1 - 6.3: Low pass filtered velocity components and temperature time series composited for mooring 87V1. Figures 6.4 - 6.6: Same time series composited for mooring 87V2.	63
Figure 7.	Figures 7.1 - 7.8: Velocity component and temperature variance density spectra.	72

List of Tables

Table 1. Launch and recovery information	5
Table 2. Statistics of the 87V1 velocity components and temperature	7
Table 3. Statistics of the 87V2 velocity components and temperature	8
Table 4. Variances of the velocity components and temperature	71

Foreword

The data presented here were collected with the assistance of several institutions. Funding support was provided by the Office of Naval Research, and ship time on the NOAA ship Townsend Cromwell was provided by the Honolulu Laboratory of the National Marine Fisheries Service. The Atlantic Oceanographic and Meteorological Laboratory, NOAA supplied three of the current meters. The moorings were prepared and initial data processing was done at the Pacific Marine Environmental Laboratory, NOAA. Instrument calibration was performed by the Northwest Regional Calibration Center, Bellevue, Washington.

1. Introduction

Two bottom moored current meter arrays were deployed on the South East Hancock Seamount ($29^{\circ} 48' N$, $179^{\circ} 04' E$) in April 1987. The purpose of the project was to observe for the first time the currents near the summit of this seamount, to determine dominant short period (10 minutes - 50 hours) constituents and variability for the current field and to provide data for future current meter array design. The period of observations was limited to 15 days because of research vessel scheduling.

Presented in this report are velocity and temperature data collected from the current meters during this deployment. The report consists of six sections. The field program is discussed in Section 2. Section 3 contains the data editing steps and presents the raw 5 minute time series, histograms and statistics. Hourly time series are presented in section 4, and low pass filtered six-hourly time series are presented in section 5. Section 6 contains the composited low pass time series for each mooring based on the time series presented in section 5. Variance density spectra for current velocities and temperatures are given in section 7.

2. Field Program

The two moorings were deployed on the South East Hancock Seamount from the NOAA ship Townsend Cromwell on 12 April 1987 and were recovered on 27 April 1987. A large scale fisheries survey was conducted concurrent with the mooring deployment. The location of the South East Hancock Seamount is shown in Figure 1 on page 3. Mooring 87V1 was deployed at or very near to the highest elevation of the seamount at $29^{\circ} 48.38' N$, $179^{\circ} 03.51' E$ in 260 meters of water. Mooring 87V2 was deployed on the flank of the seamount at $29^{\circ} 48.89' N$, $179^{\circ} 03.25' E$ at a depth of approximately 390 meters. The two moorings are separated laterally by approximately 1030 meters. Originally, this second mooring was intended to be anchored at a depth of 350 meters. However, the observed temperature and pressure records indicate that the actual depth exceeded the intended depth by approximately 50 meters. It is believed that the anchor and mooring failed to take hold at the intended depth due to an unexpectedly steep bottom slope on the seamount flank. A schematic of the configuration of the moorings as actually deployed is shown in Figure 2 on page 4.

Mooring 87V1 had 5 Aanderaa RCM-4 current meters mounted at 50, 165, 215, 255 and 260 meters below the surface. In this report, these meters are given the labels V11, V12, V13, V14 and V15 respectively. Mooring 87V2 had 3 Aanderaa RCM-4 current meters mounted at 215, 265 and 390 meters below the surface. The design depths had actually been 165, 215 and 340 meters respectively. The meters on 87V2 were given the labels V23, V25 and V26 to simplify comparisons with the meters on 87V1 that were situated at about the same depths.

The launch and recovery data for each mooring are summarized in Table 1 on page 5.




Figure 1. Location of the South East Hancock Seamount.

SOUTHEAST HANCOCK SEAMOUNT




Figure 2. Deployment configuration of moorings 87V1 and 87V2.: The depths in parentheses for mooring 87V2 are the design depths. The actual deployment depths are noted to the right of the meter labels. Vertical axis: 1 inch = 100 meters. Horizontal axis: Not to scale.

Mooring ID	Location Lat/Long	Bottom Depth (M)	Launch Time GMT	Recovery Time GMT	Current Meter Depth (M)	RCM-4 Current Meter Serial #
87V1	29° 48.38' N 179° 3.51' E	260	0500 12 Apr 87	1920 27 Apr 87	50 165 215 255 260	2760 0407 5211 5644 5643
87V2	29° 48.89' N 179° 3.25' E	390	2220 12 Apr 87	2045 27 Apr 87	215 265 390	0408 2759 5645

Table 1. Launch and recovery information

3. Data Editing

The initial post-processing of the data was done at Pacific Marine Environmental Laboratory using three programs: CM1, CME and C2C. Program CM1 was used to buffer the data off the cartridge and transform it into scientific units. Program CME was used to determine data start and stop times and to remove obviously wrong values. Program C2C was used to remove large obviously erroneous spikes and questionable zero speeds. The data were then sent by 9 track tape to the Naval Postgraduate School for final editing and processing. The current meters stored data in 5 minute intervals. The processed current velocity data has been represented here in easterly (U) and northerly (V) components.

The statistics of the basic 5-minute velocity components and temperature data are shown in Table 2 on page 7 and Table 3 on page 8, and histograms and time series are presented in Figure 3 on page 9. Due to a possible bearing failure, current meter V25 recorded a large number of zero speeds in the north and east velocity components, but the temperature data from this meter are unaffected by the problem.

V11				
	Mean	St. Dev.	Skewness	Kurtosis
U (Cm/Sec)	-9.336	9.337	0.073	2.962
V (Cm/Sec)	1.246	6.445	-0.846	4.124
Temp (Deg C)	18.023	0.707	-5.763	191.313
V12				
	Mean	St. Dev.	Skewness	Kurtosis
U (Cm/Sec)	-11.641	6.327	0.498	4.165
V (Cm/Sec)	4.903	6.911	-0.453	3.144
Temp (Deg C)	15.460	0.381	-20.596	811.999
V13				
	Mean	St. Dev.	Skewness	Kurtosis
U (Cm/Sec)	-9.436	6.861	0.129	3.042
V (Cm/Sec)	6.267	6.498	-0.554	2.941
Temp (Deg C)	14.740	0.344	-21.554	1175.635
V14				
	Mean	St. Dev.	Skewness	Kurtosis
U (Cm/Sec)	-10.902	7.896	0.143	2.761
V (Cm/Sec)	7.456	6.786	-0.342	2.771
Temp (Deg C)	13.983	0.312	-13.683	1113.496
V15				
	Mean	St. Dev.	Skewness	Kurtosis
U (Cm/Sec)	-10.356	8.013	0.241	3.645
V (Cm/Sec)	6.908	6.818	-0.548	3.016
Temp (Deg C)	13.679	0.309	-11.209	804.698

Table 2. Statistics of the 87V1 velocity components and temperature

V23				
	Mean	St. Dev.	Skewness	Kurtosis
U (Cm Sec)	-9.277	6.122	6.001	2.790
V (Cm Sec)	5.905	5.552	-0.155	2.427
Temp (Deg C)	14.643	0.280	-19.168	1398.333
V25				
	Mean	St. Dev.	Skewness	Kurtosis
U (Cm Sec)	-4.600	7.436	-0.729	2.966
V (Cm Sec)	1.914	4.796	0.488	3.759
Temp (Deg C)	13.910	0.328	-8.960	345.262
V26				
	Mean	St. Dev.	Skewness	Kurtosis
U (Cm Sec)	-2.255	8.428	0.111	2.509
V (Cm Sec)	1.509	5.674	1.881	7.491
Temp (Deg C)	11.325	0.522	-1.204	10.087

Table 3. Statistics of the 87V2 velocity components and temperature

Figure 3. Figures 3.1 - 3.24: Histograms of the velocity components and temperature of the basic 5 minute interval data set. Figures 3.25 - 3.32: Time series of the same data.

FIGURE 3.1

V11 EAST

NO. OF POINTS - 4492 BIN SIZE - 2.0 CM/SEC

BIN	BOUND	FREQ	PERCENT
1	<-40.0	0	0.00
2	-38.0	0	0.00
3	-36.0	2	0.04
4	-34.0	5	0.11
5	-32.0	11	0.24
6	-30.0	33	0.73 X
7	-28.0	49	1.09 X
8	-26.0	65	1.45 X
9	-24.0	114	2.54 XXX
10	-22.0	149	3.32 XXX
11	-20.0	174	3.87 XXXX
12	-18.0	203	4.52 XXXXX
13	-16.0	243	5.41 XXXXX
14	-14.0	321	7.15 XXXXXX
15	-12.0	321	7.15 XXXXXXX
16	-10.0	416	9.26 XXXXXXXX
17	-8.0	418	9.31 XXXXXXXX
18	-6.0	340	7.57 XXXXXXX
19	-4.0	315	7.01 XXXXXXX
20	-2.0	346	7.70 XXXXXXX
21	0.0	296	6.59 XXXXXXX
22	2.0	228	5.08 XXXXX
23	4.0	68	1.51 XX
24	6.0	112	2.49 XX
25	8.0	86	1.91 XX
26	10.0	65	1.45 X
27	12.0	31	0.69 X
28	14.0	35	0.78 X
29	16.0	32	0.71 X
30	18.0	10	0.22
31	20.0	3	0.07
32	22.0	1	0.02
33	24.0	0	0.00
34	26.0	0	0.00
35	28.0	0	0.00
36	30.0	0	0.00
37	32.0	0	0.00
38	34.0	0	0.00
39	36.0	0	0.00
40	38.0	0	0.00
41	40.0	0	0.00
42	>40.0	0	0.00

FIGURE 3.2

V11 NORTH

NO. OF POINTS = 4492 BIN SIZE = 2.0 CM/SEC

BIN	BOUND	FREQ	PERCENT	
1	<-40.0	0	0.00	
2	-38.0	0	0.00	
3	-36.0	0	0.00	
4	-34.0	0	0.00	
5	-32.0	0	0.00	
6	-30.0	0	0.00	
7	-28.0	0	0.00	
8	-26.0	0	0.00	
9	-24.0	0	0.00	
10	-22.0	1	0.02	
11	-20.0	10	0.22	
12	-18.0	27	0.60	X
13	-16.0	58	1.29	X
14	-14.0	69	1.54	XX
15	-12.0	89	1.98	XX
16	-10.0	112	2.49	XX
17	-8.0	80	1.78	XX
18	-6.0	91	2.03	XX
19	-4.0	126	2.80	XXX
20	-2.0	187	4.16	XXXX
21	0.0	447	9.95	XXXXXXXXXX
22	2.0	1181	26.29	XXXXXXXXXXXXXXXXXXXXXXXXXXXX
23	4.0	530	11.80	XXXXXXXXXXXXXX
24	6.0	550	12.24	XXXXXXXXXXXXXX
25	8.0	360	8.01	XXXXXXX
26	10.0	277	6.17	XXXXXX
27	12.0	170	3.78	XXXX
28	14.0	102	2.27	XX
29	16.0	20	0.45	
30	18.0	5	0.11	
31	20.0	0	0.00	
32	22.0	0	0.00	
33	24.0	0	0.00	
34	26.0	0	0.00	
35	28.0	0	0.00	
36	30.0	0	0.00	
37	32.0	0	0.00	
38	34.0	0	0.00	
39	36.0	0	0.00	
40	38.0	0	0.00	
41	40.0	0	0.00	
42	>40.0	0	0.00	

FIGURE 3.3

V11 TEMPERATURE

NO. OF POINTS - 4492 BIN SIZE - .1 DEG C

BIN	BOUND	FREQ	PERCENT	
1	<16.0	0	0.00	
2	16.1	0	0.00	
3	16.2	0	0.00	
4	16.3	0	0.00	
5	16.4	3	0.07	
6	16.5	10	0.22	
7	16.6	5	0.11	
8	16.7	18	0.40	
9	16.8	41	0.91	X
10	16.9	58	1.29	X
11	17.0	69	1.54	XX
12	17.1	98	2.18	XX
13	17.2	147	3.27	XXX
14	17.3	164	3.65	XXXX
15	17.4	234	5.21	XXXXX
16	17.5	186	4.14	XXXX
17	17.6	183	4.07	XXXX
18	17.7	204	4.54	XXXXX
19	17.8	229	5.10	XXXXX
20	17.9	239	5.32	XXXXX
21	18.0	168	3.74	XXXX
22	18.1	183	4.07	XXXX
23	18.2	357	7.95	XXXXXXXX
24	18.3	315	7.01	XXXXXXXX
25	18.4	234	5.21	XXXXX
26	18.5	256	5.70	XXXXXX
27	18.6	233	5.19	XXXXX
28	18.7	252	5.61	XXXXXX
29	18.8	248	5.52	XXXXXX
30	18.9	99	2.20	XX
31	19.0	91	2.03	XX
32	19.1	52	1.16	X
33	19.2	24	0.53	X
34	19.3	22	0.49	
35	19.4	17	0.38	
36	19.5	6	0.13	
37	19.6	3	0.07	
38	19.7	5	0.11	
39	19.8	5	0.11	
40	19.9	1	0.02	
41	20.0	5	0.11	
42	>20.0	28	0.62	X

FIGURE 3.4

V12 EAST

NO. OF POINTS = 4492 BIN SIZE = 2.0 CM/SEC

BIN	BOUND	FREQ	PERCENT	
1	<-40.0	0	0.00	
2	-38.0	0	0.00	
3	-36.0	0	0.00	
4	-34.0	0	0.00	
5	-32.0	0	0.00	
6	-30.0	0	0.00	
7	-28.0	8	0.18	
8	-26.0	10	0.22	
9	-24.0	86	1.91	XX
10	-22.0	131	2.92	XXX
11	-20.0	171	3.81	XXXX
12	-18.0	260	5.79	XXXXXX
13	-16.0	343	7.64	XXXXXXXX
14	-14.0	465	10.35	XXXXXXXXXX
15	-12.0	646	14.38	XXXXXXXXXXXX
16	-10.0	724	16.12	XXXXXXXXXXXXXXXX
17	-8.0	616	13.71	XXXXXXXXXXXXXX
18	-6.0	405	9.02	XXXXXXXXXX
19	-4.0	249	5.54	XXXXXX
20	-2.0	107	2.38	XX
21	0.0	61	1.36	X
22	2.0	46	1.02	X
23	4.0	43	0.96	X
24	6.0	46	1.02	X
25	8.0	38	0.85	X
26	10.0	23	0.51	X
27	12.0	10	0.22	
28	14.0	4	0.09	
29	16.0	0	0.00	
30	18.0	0	0.00	
31	20.0	0	0.00	
32	22.0	0	0.00	
33	24.0	0	0.00	
34	26.0	0	0.00	
35	28.0	0	0.00	
36	30.0	0	0.00	
37	32.0	0	0.00	
38	34.0	0	0.00	
39	36.0	0	0.00	
40	38.0	0	0.00	
41	40.0	0	0.00	
42	>40.0	0	0.00	

FIGURE 3.5

V12 NORTH

NO. OF POINTS = 4492 BIN SIZE = 2.0 CM/SEC

BIN	BOUND	FREQ	PERCENT
1	<-40.0	0	0.00
2	-38.0	0	0.00
3	-36.0	0	0.00
4	-34.0	0	0.00
5	-32.0	0	0.00
6	-30.0	0	0.00
7	-28.0	0	0.00
8	-26.0	0	0.00
9	-24.0	0	0.00
10	-22.0	0	0.00
11	-20.0	3	0.07
12	-18.0	9	0.20
13	-16.0	10	0.22
14	-14.0	16	0.36
15	-12.0	24	0.53 X
16	-10.0	46	1.02 X
17	-8.0	82	1.83 XX
18	-6.0	141	3.14 XXX
19	-4.0	144	3.21 XXX
20	-2.0	253	5.63 XXXXXX
21	0.0	324	7.21 XXXXXXXX
22	2.0	368	8.19 XXXXXXXXX
23	4.0	435	9.68 XXXXXXXXXXX
24	6.0	527	11.73 XXXXXXXXXXXX
25	8.0	510	11.35 XXXXXXXXXXX
26	10.0	441	9.82 XXXXXXXXXXX
27	12.0	470	10.46 XXXXXXXXXXX
28	14.0	356	7.93 XXXXXXXXX
29	16.0	221	4.92 XXXXX
30	18.0	68	1.51 XX
31	20.0	21	0.47
32	22.0	11	0.24
33	24.0	6	0.13
34	26.0	3	0.07
35	28.0	2	0.04
36	30.0	1	0.02
37	32.0	0	0.00
38	34.0	0	0.00
39	36.0	0	0.00
40	38.0	0	0.00
41	40.0	0	0.00
42	>40.0	0	0.00

FIGURE 3.6

V12 TEMPERATURE

NO. OF POINTS = 4492 BIN SIZE = .1 DEG C

BIN	BOUND	FREQ	PERCENT	
1	<14.0	0	0.00	
2	14.1	0	0.00	
3	14.2	0	0.00	
4	14.3	0	0.00	
5	14.4	0	0.00	
6	14.5	0	0.00	
7	14.6	0	0.00	
8	14.7	0	0.00	
9	14.8	13	0.29	
10	14.9	26	0.58	X
11	15.0	89	1.98	XX
12	15.1	218	4.85	XXXXX
13	15.2	372	8.28	XXXXXXXX
14	15.3	501	11.15	XXXXXXXXXXXX
15	15.4	739	16.45	XXXXXXXXXXXXXXXX
16	15.5	647	14.40	XXXXXXXXXXXXXX
17	15.6	613	13.65	XXXXXXXXXXXXXX
18	15.7	500	11.13	XXXXXXXXXXXX
19	15.8	392	8.73	XXXXXXXXXX
20	15.9	149	3.32	XXX
21	16.0	78	1.74	XX
22	16.1	38	0.85	X
23	16.2	35	0.78	X
24	16.3	37	0.82	X
25	16.4	25	0.56	X
26	16.5	13	0.29	
27	16.6	7	0.16	
28	16.7	0	0.00	
29	16.8	0	0.00	
30	16.9	0	0.00	
31	17.0	0	0.00	
32	17.1	0	0.00	
33	17.2	0	0.00	
34	17.3	0	0.00	
35	17.4	0	0.00	
36	17.5	0	0.00	
37	17.6	0	0.00	
38	17.7	0	0.00	
39	17.8	0	0.00	
40	17.9	0	0.00	
41	18.0	0	0.00	
42	>18.0	0	0.00	

FIGURE 3.7

V13 EAST

NO. OF POINTS = 4493 BIN SIZE = 2.0 CM/SEC

BIN	BOUND	FREQ	PERCENT	
1	<-40.0	0	0.00	
2	-38.0	0	0.00	
3	-36.0	0	0.00	
4	-34.0	0	0.00	
5	-32.0	0	0.00	
6	-30.0	2	0.04	
7	-28.0	11	0.24	
8	-26.0	16	0.36	
9	-24.0	31	0.69	X
10	-22.0	69	1.54	XX
11	-20.0	143	3.18	XXX
12	-18.0	215	4.79	XXXX
13	-16.0	271	6.03	XXXXX
14	-14.0	384	8.55	XXXXXXXX
15	-12.0	452	10.06	XXXXXXXXX
16	-10.0	506	11.26	XXXXXXXXXX
17	-8.0	498	11.08	XXXXXXXXXXX
18	-6.0	541	12.04	XXXXXXXXXXXX
19	-4.0	488	10.86	XXXXXXXXXXXX
20	-2.0	289	6.43	XXXXX
21	0.0	206	4.58	XXXX
22	2.0	117	2.60	XXX
23	4.0	91	2.03	XX
24	6.0	73	1.62	XX
25	8.0	53	1.18	X
26	10.0	26	0.58	X
27	12.0	10	0.22	
28	14.0	1	0.02	
29	16.0	0	0.00	
30	18.0	0	0.00	
31	20.0	0	0.00	
32	22.0	0	0.00	
33	24.0	0	0.00	
34	26.0	0	0.00	
35	28.0	0	0.00	
36	30.0	0	0.00	
37	32.0	0	0.00	
38	34.0	0	0.00	
39	36.0	0	0.00	
40	38.0	0	0.00	
41	40.0	0	0.00	
42	>40.0	0	0.00	

FIGURE 3.8

V13 NORTH

NO. OF POINTS = 4493 BIN SIZE = 2.0 CM/SEC

BIN	BOUND	FREQ	PERCENT	
1	<-40.0	0	0.00	
2	-38.0	0	0.00	
3	-36.0	0	0.00	
4	-34.0	0	0.00	
5	-32.0	0	0.00	
6	-30.0	0	0.00	
7	-28.0	0	0.00	
8	-26.0	0	0.00	
9	-24.0	0	0.00	
10	-22.0	0	0.00	
11	-20.0	0	0.00	
12	-18.0	0	0.00	
13	-16.0	2	0.04	
14	-14.0	5	0.11	
15	-12.0	17	0.38	
16	-10.0	22	0.49	
17	-8.0	74	1.65	XX
18	-6.0	116	2.58	XXX
19	-4.0	157	3.49	XXX
20	-2.0	161	3.58	XXXX
21	0.0	203	4.52	XXXXXX
22	2.0	321	7.14	XXXXXXXX
23	4.0	371	8.26	XXXXXXXXX
24	6.0	483	10.75	XXXXXXXXXXXX
25	8.0	553	12.31	XXXXXXXXXXXXXX
26	10.0	602	13.40	XXXXXXXXXXXXXX
27	12.0	538	11.97	XXXXXXXXXXXXXY
28	14.0	442	9.84	XXXXXXXXXXXX
29	16.0	260	5.79	XXXXXXX
30	18.0	102	2.27	XX
31	20.0	55	1.22	X
32	22.0	9	0.20	
33	24.0	0	0.00	
34	26.0	0	0.00	
35	28.0	0	0.00	
36	30.0	0	0.00	
37	32.0	0	0.00	
38	34.0	0	0.00	
39	36.0	0	0.00	
40	38.0	0	0.00	
41	40.0	0	0.00	
42	>40.0	0	0.00	

FIGURE 3.9

V13 TEMPERATURE

NO. OF POINTS - 4493 BIN SIZE - .1 DEG C

BIN	BOUND	FREQ	PERCENT
1	<13.0	0	0.00
2	13.1	0	0.00
3	13.2	0	0.00
4	13.3	0	0.00
5	13.4	0	0.00
6	13.5	0	0.00
7	13.6	0	0.00
8	13.7	0	0.00
9	13.8	0	0.00
10	13.9	2	0.04
11	14.0	8	0.18
12	14.1	20	0.45
13	14.2	60	1.34 X
14	14.3	152	3.38 XXX
15	14.4	304	6.77 XXXXXXX
16	14.5	364	8.10 XXXXXXXX
17	14.6	504	11.22 XXXXXYYXXXX
18	14.7	534	11.89 XXXXXXXXXXXXXX
19	14.8	515	11.46 XXXXXXXXXXXXXX
20	14.9	638	14.20 XXXXXXXXXXXXXXX
21	15.0	581	12.93 XXXXXXXXXXXXXXX
22	15.1	411	9.15 XXXXXXXXXX
23	15.2	213	4.74 XXXXX
24	15.3	127	2.83 XXX
25	15.4	47	1.05 X
26	15.5	9	0.20
27	15.6	4	0.09
28	15.7	0	0.00
29	15.8	0	0.00
30	15.9	0	0.00
31	16.0	0	0.00
32	16.1	0	0.00
33	16.2	0	0.00
34	16.3	0	0.00
35	16.4	0	0.00
36	16.5	0	0.00
37	16.6	0	0.00
38	16.7	0	0.00
39	16.8	0	0.00
40	16.9	0	0.00
41	17.0	0	0.00
42	>17.0	0	0.00

FIGURE 3.10

V14 EAST

NO. OF POINTS = 4493 BIN SIZE = 2.0 CM/SEC

BIN	BOUND	FREQ	PERCENT
1	<-40.0	0	0.00
2	-38.0	0	0.00
3	-36.0	0	0.00
4	-34.0	0	0.00
5	-32.0	4	0.09
6	-30.0	18	0.40
7	-28.0	23	0.51 X
8	-26.0	33	0.73 X
9	-24.0	109	2.43 XX
10	-22.0	187	4.16 XXXX
11	-20.0	239	5.32 XXXXX
12	-18.0	247	5.50 XXXXX
13	-16.0	341	7.59 XXXXXXXX
14	-14.0	354	7.88 XXXXXXXX
15	-12.0	446	9.93 XXXXXXXXXXX
16	-10.0	490	10.91 XXXXXXXXXXXX
17	-8.0	465	10.35 XXXXXXXXXXX
18	-6.0	384	8.55 XXXXXXXXXXX
19	-4.0	319	7.10 XXXXXXX
20	-2.0	246	5.48 XXXXX
21	0.0	150	3.34 XXX
22	2.0	153	3.41 XXX
23	4.0	111	2.47 XX
24	6.0	90	2.00 XX
25	8.0	51	1.14 X
26	10.0	19	0.42
27	12.0	9	0.20
28	14.0	5	0.11
29	16.0	0	0.00
30	18.0	0	0.00
31	20.0	0	0.00
32	22.0	0	0.00
33	24.0	0	0.00
34	26.0	0	0.00
35	28.0	0	0.00
36	30.0	0	0.00
37	32.0	0	0.00
38	34.0	0	0.00
39	36.0	0	0.00
40	38.0	0	0.00
41	40.0	0	0.00
42	>40.0	0	0.00

FIGURE 3.11

V14 NORTH

NO. OF POINTS - 4493 BIN SIZE - 2.0 CM/SEC

BIN	BOUND	FREQ	PERCENT	
1	<-40.0	0	0.00	
2	-38.0	0	0.00	
3	-36.0	0	0.00	
4	-34.0	0	0.00	
5	-32.0	0	0.00	
6	-30.0	0	0.00	
7	-28.0	0	0.00	
8	-26.0	0	0.00	
9	-24.0	0	0.00	
10	-22.0	0	0.00	
11	-20.0	0	0.00	
12	-18.0	0	0.00	
13	-16.0	0	0.00	
14	-14.0	0	0.00	
15	-12.0	6	0.13	
16	-10.0	21	0.47	
17	-8.0	36	0.80	X
18	-6.0	82	1.83	XX
19	-4.0	162	3.61	XXXX
20	-2.0	194	4.32	XXXX
21	0.0	161	3.58	XXXX
22	2.0	288	6.41	XXXXXX
23	4.0	349	7.77	XXXXXXXX
24	6.0	425	9.46	XXXXXXXXX
25	8.0	462	10.28	XXXXXXXXXX
26	10.0	532	11.84	XXXXXXXXXXXX
27	12.0	553	12.31	XXXXXXXXXXXX
28	14.0	476	10.59	XXXXXXXXXXXX
29	16.0	372	8.28	XXXXXXXX
30	18.0	203	4.52	XXXXX
31	20.0	101	2.25	XX
32	22.0	35	0.78	X
33	24.0	21	0.47	
34	26.0	8	0.18	
35	28.0	5	0.11	
36	30.0	1	0.02	
37	32.0	0	0.00	
38	34.0	0	0.00	
39	36.0	0	0.00	
40	38.0	0	0.00	
41	40.0	0	0.00	
42	>40.0	0	0.00	

FIGURE 3.12

V14 TEMPERATURE

NO. OF POINTS - 4493 BIN SIZE - .1 DEG C

BIN	BOUND	FREQ	PERCENT
1	<12.0	0	0.00
2	12.1	0	0.00
3	12.2	0	0.00
4	12.3	0	0.00
5	12.4	0	0.00
6	12.5	0	0.00
7	12.6	0	0.00
8	12.7	0	0.00
9	12.8	0	0.00
10	12.9	0	0.00
11	13.0	0	0.00
12	13.1	0	0.00
13	13.2	1	0.02
14	13.3	8	0.18
15	13.4	55	1.22 X
16	13.5	99	2.20 XX
17	13.6	182	4.05 XXX
18	13.7	349	7.77 XXXXXXXX
19	13.8	506	11.26 XXXXXXXXXXX
20	13.9	517	11.51 XXXXXXXXXXX
21	14.0	559	12.44 XXXXXXXXXXX
22	14.1	667	14.85 XXXXXXXXXXXXXXX
23	14.2	559	12.44 XXXXXXXXXXXXXXX
24	14.3	394	8.77 XXXXXXXX
25	14.4	286	6.37 XXXXXX
26	14.5	134	2.98 XXX
27	14.6	120	2.67 XXX
28	14.7	57	1.27 X
29	14.8	0	0.00
30	14.9	0	0.00
31	15.0	0	0.00
32	15.1	0	0.00
33	15.2	0	0.00
34	15.3	0	0.00
35	15.4	0	0.00
36	15.5	0	0.00
37	15.6	0	0.00
38	15.7	0	0.00
39	15.8	0	0.00
40	15.9	0	0.00
41	16.0	0	0.00
42	>16.0	0	0.00

FIGURE 3.13

V15 EAST

NO. OF POINTS - 4492 BIN SIZE - 2.0 CM/SEC

BIN	BOUND	FREQ	PERCENT	
1	<-40.0	0	0.00	
2	-38.0	0	0.00	
3	-36.0	0	0.00	
4	-34.0	0	0.00	
5	-32.0	0	0.00	
6	-30.0	10	0.22	
7	-28.0	30	0.67	X
8	-26.0	34	0.76	X
9	-24.0	104	2.32	XX
10	-22.0	182	4.05	XXXX
11	-20.0	208	4.63	XXXXX
12	-18.0	235	5.23	XXXXX
13	-16.0	315	7.01	XXXXXXX
14	-14.0	345	7.68	XXXXXXXX
15	-12.0	367	8.17	XXXXXXXX
16	-10.0	442	9.84	XXXXXXXXX
17	-8.0	494	11.00	XXXXXXXXXX
18	-6.0	453	10.08	XXXXXXXXX
19	-4.0	383	8.53	XXXXXXX
20	-2.0	256	5.70	XXXXX
21	0.0	210	4.67	XXXX
22	2.0	155	3.45	XXX
23	4.0	102	2.27	XX
24	6.0	70	1.56	XX
25	8.0	43	0.96	X
26	10.0	24	0.53	X
27	12.0	12	0.27	
28	14.0	6	0.13	
29	16.0	6	0.13	
30	18.0	1	0.02	
31	20.0	0	0.00	
32	22.0	0	0.00	
33	24.0	0	0.00	
34	26.0	0	0.00	
35	28.0	0	0.00	
36	30.0	0	0.00	
37	32.0	0	0.00	
38	34.0	5	0.11	
39	36.0	0	0.00	
40	38.0	0	0.00	
41	40.0	0	0.00	
42	>40.0	0	0.00	

FIGURE 3.14

V15 NORTH

NO. OF POINTS - 4492 BIN SIZE - 2.0 CM/SEC

BIN	BOUND	FREQ	PERCENT	
1	<-40.0	0	0.00	
2	-38.0	0	0.00	
3	-36.0	0	0.00	
4	-34.0	0	0.00	
5	-32.0	0	0.00	
6	-30.0	0	0.00	
7	-28.0	0	0.00	
8	-26.0	0	0.00	
9	-24.0	0	0.00	
10	-22.0	1	0.02	
11	-20.0	1	0.02	
12	-18.0	0	0.00	
13	-16.0	0	0.00	
14	-14.0	1	0.02	
15	-12.0	10	0.22	
16	-10.0	51	1.14	X
17	-8.0	78	1.74	XX
18	-6.0	105	2.34	XX
19	-4.0	114	2.54	XXX
20	-2.0	145	3.23	XXX
21	0.0	217	4.83	XXXXX
22	2.0	277	6.17	XXXXXX
23	4.0	379	8.44	XXXXXXXX
24	6.0	431	9.59	XXXXXXXXXX
25	8.0	453	10.08	XXXXXXXXXXX
26	10.0	552	12.29	XXXXXXXXXXXX
27	12.0	563	12.53	XXXXXXXXXXXXX
28	14.0	519	11.55	XXXXXXXXXXXX
29	16.0	328	7.30	XXXXXXX
30	18.0	168	3.74	XXXX
31	20.0	58	1.29	X
32	22.0	30	0.67	X
33	24.0	9	0.20	
34	26.0	0	0.00	
35	28.0	1	0.02	
36	30.0	0	0.00	
37	32.0	0	0.00	
38	34.0	1	0.02	
39	36.0	0	0.00	
40	38.0	0	0.00	
41	40.0	0	0.00	
42	>40.0	0	0.00	

FIGURE 3.15

V15 TEMPERATURE

NO. OF POINTS = 4492 BIN SIZE = .1 DEG C

BIN	BOUND	FREQ	PERCENT	
1	<12.0	0	0.00	
2	12.1	0	0.00	
3	12.2	0	0.00	
4	12.3	0	0.00	
5	12.4	0	0.00	
6	12.5	0	0.00	
7	12.6	0	0.00	
8	12.7	0	0.00	
9	12.8	0	0.00	
10	12.9	0	0.00	
11	13.0	15	0.33	
12	13.1	59	1.31	X
13	13.2	88	1.96	XX
14	13.3	203	4.52	XXXXX
15	13.4	307	6.83	XXXXXXX
16	13.5	483	10.75	XXXXXXXXXX
17	13.6	696	15.49	XXXXXXXXXXXXXX
18	13.7	548	12.20	XXXXXXXXXXXXXX
19	13.8	502	11.18	XXXXXXXXXXXXXX
20	13.9	596	13.27	XXXXXXXXXXXXXX
21	14.0	366	8.15	XXXXXXXXXX
22	14.1	290	6.46	XXXXXX
23	14.2	228	5.08	XXXXX
24	14.3	76	1.69	XX
25	14.4	28	0.62	X
26	14.5	7	0.16	
27	14.6	0	0.00	
28	14.7	0	0.00	
29	14.8	0	0.00	
30	14.9	0	0.00	
31	15.0	0	0.00	
32	15.1	0	0.00	
33	15.2	0	0.00	
34	15.3	0	0.00	
35	15.4	0	0.00	
36	15.5	0	0.00	
37	15.6	0	0.00	
38	15.7	0	0.00	
39	15.8	0	0.00	
40	15.9	0	0.00	
41	16.0	0	0.00	
42	>16.0	0	0.00	

FIGURE 3.16

V23 EAST

NO. OF POINTS - 4302 BIN SIZE - 2.0 CM/SEC

BIN	BOUND	FREQ	PERCENT	
1	<-40.0	0	0.00	
2	-38.0	0	0.00	
3	-36.0	0	0.00	
4	-34.0	0	0.00	
5	-32.0	0	0.00	
6	-30.0	0	0.00	
7	-28.0	0	0.00	
8	-26.0	3	0.07	
9	-24.0	37	0.86	X
10	-22.0	59	1.37	X
11	-20.0	71	1.65	XX
12	-18.0	168	3.91	XXXX
13	-16.0	228	5.30	XXXXXX
14	-14.0	383	8.90	XXXXXXXX
15	-12.0	543	12.62	XXXXXXXXXXXX
16	-10.0	491	11.41	XXXXXXXXXXXX
17	-8.0	507	11.79	XXXXXXXXXXXX
18	-6.0	529	12.30	XXXXXXXXXXXX
19	-4.0	411	9.55	XXXXXXXXXXXX
20	-2.0	322	7.48	XXXXXXX
21	0.0	281	6.53	XXXXXXX
22	2.0	137	3.18	XXX
23	4.0	65	1.51	XX
24	6.0	49	1.14	X
25	8.0	14	0.33	
26	10.0	3	0.07	
27	12.0	1	0.02	
28	14.0	0	0.00	
29	16.0	0	0.00	
30	18.0	0	0.00	
31	20.0	0	0.00	
32	22.0	0	0.00	
33	24.0	0	0.00	
34	26.0	0	0.00	
35	28.0	0	0.00	
36	30.0	0	0.00	
37	32.0	0	0.00	
38	34.0	0	0.00	
39	36.0	0	0.00	
40	38.0	0	0.00	
41	40.0	0	0.00	
42	>40.0	0	0.00	

FIGURE 3.17

V23 NORTH

NO. OF POINTS - 4302 BIN SIZE - 2.0 CM/SEC

BIN	BOUND	FREQ	PERCENT
1	<-40.0	0	0.00
2	-38.0	0	0.00
3	-36.0	0	0.00
4	-34.0	0	0.00
5	-32.0	0	0.00
6	-30.0	0	0.00
7	-28.0	0	0.00
8	-26.0	0	0.00
9	-24.0	0	0.00
10	-22.0	0	0.00
11	-20.0	0	0.00
12	-18.0	0	0.00
13	-16.0	0	0.00
14	-14.0	0	0.00
15	-12.0	0	0.00
16	-10.0	1	0.02
17	-8.0	8	0.19
18	-6.0	31	0.72 X
19	-4.0	140	3.25 XXX
20	-2.0	255	5.93 XXXXX
21	0.0	272	6.32 XXXXX
22	2.0	371	8.62 XXXXXXXXX
23	4.0	473	10.99 XXXXXXXXXXX
24	6.0	550	12.78 XXXXXXXXXXX
25	8.0	583	13.55 XXXXXXXXXXX
26	10.0	511	11.88 XXXXXXXXXXX
27	12.0	509	11.83 XXXXXXXXXXX
28	14.0	327	7.60 XXXXXX
29	16.0	159	3.70 XXX
30	18.0	91	2.12 XX
31	20.0	19	0.44
32	22.0	2	0.05
33	24.0	0	0.00
34	26.0	0	0.00
35	28.0	0	0.00
36	30.0	0	0.00
37	32.0	0	0.00
38	34.0	0	0.00
39	36.0	0	0.00
40	38.0	0	0.00
41	40.0	0	0.00
42	>40.0	0	0.00

FIGURE 3.18

V23 TEMPERATURE

NO. OF POINTS = 4302 BIN SIZE = .1 DEG C

BIN	BOUND	FREQ	PERCENT
1	<13.0	0	0.00
2	13.1	0	0.00
3	13.2	0	0.00
4	13.3	0	0.00
5	13.4	0	0.00
6	13.5	0	0.00
7	13.6	0	0.00
8	13.7	0	0.00
9	13.8	0	0.00
10	13.9	3	0.07
11	14.0	8	0.19
12	14.1	9	0.21
13	14.2	46	1.07 X
14	14.3	215	5.00 XXXXX
15	14.4	431	10.02 XXXXXXXXXXXX
16	14.5	532	12.37 XXXXXXXXXXXXXX
17	14.6	683	15.88 XXXXXXXXXXXXXXXX
18	14.7	614	14.27 XXXXXXXXXXXXXXX
19	14.8	574	13.34 XXXXXXXXXXXXXXX
20	14.9	549	12.76 XXXXXXXXXXXXXXX
21	15.0	352	8.18 XXXXXXXX
22	15.1	204	4.74 XXXXX
23	15.2	59	1.37 X
24	15.3	7	0.16
25	15.4	13	0.30
26	15.5	3	0.07
27	15.6	0	0.00
28	15.7	0	0.00
29	15.8	0	0.00
30	15.9	0	0.00
31	16.0	0	0.00
32	16.1	0	0.00
33	16.2	0	0.00
34	16.3	0	0.00
35	16.4	0	0.00
36	16.5	0	0.00
37	16.6	0	0.00
38	16.7	0	0.00
39	16.8	0	0.00
40	16.9	0	0.00
41	17.0	0	0.00
42	>17.0	0	0.00

FIGURE 3.19

V25 EAST

NO. OF POINTS = 4302 BIN SIZE = 2.0 CM/SEC

BIN	BOUND	FREQ	PERCENT	
1	<-40.0	0	0.00	
2	-38.0	0	0.00	
3	-36.0	0	0.00	
4	-34.0	0	0.00	
5	-32.0	0	0.00	
6	-30.0	0	0.00	
7	-28.0	0	0.00	
8	-26.0	10	0.23	
9	-24.0	27	0.63	X
10	-22.0	39	0.91	X
11	-20.0	88	2.05	XX
12	-18.0	136	3.16	XXX
13	-16.0	127	2.95	XXX
14	-14.0	183	4.25	XXXX
15	-12.0	221	5.14	XXXXX
16	-10.0	224	5.21	XXXXX
17	-8.0	272	6.32	XXXXXX
18	-6.0	188	4.37	XXXX
19	-4.0	171	3.97	XXXX
20	-2.0	177	4.11	XXXX
21	0.0	210	4.88	XXXXX
22	2.0	1953	45.40	XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX
23	4.0	80	1.86	XX
24	6.0	40	0.93	X
25	8.0	44	1.02	X
26	10.0	58	1.35	X
27	12.0	33	0.77	X
28	14.0	16	0.37	
29	16.0	3	0.07	
30	18.0	2	0.05	
31	20.0	0	0.00	
32	22.0	0	0.00	
33	24.0	0	0.00	
34	26.0	0	0.00	
35	28.0	0	0.00	
36	30.0	0	0.00	
37	32.0	0	0.00	
38	34.0	0	0.00	
39	36.0	0	0.00	
40	38.0	0	0.00	
41	40.0	0	0.00	
42	>40.0	0	0.00	

FIGURE 3.20

V25 NORTH

NO. OF POINTS = 4302 BIN SIZE = 2.0 CM/SEC

BIN	BOUND	FREQ	PERCENT	
1	<-40.0	0	0.00	
2	-38.0	0	0.00	
3	-36.0	0	0.00	
4	-34.0	0	0.00	
5	-32.0	0	0.00	
6	-30.0	0	0.00	
7	-28.0	0	0.00	
8	-26.0	0	0.00	
9	-24.0	0	0.00	
10	-22.0	0	0.00	
11	-20.0	0	0.00	
12	-18.0	0	0.00	
13	-16.0	0	0.00	
14	-14.0	0	0.00	
15	-12.0	10	0.23	
16	-10.0	35	0.81	X
17	-8.0	60	1.39	X
18	-6.0	82	1.91	XX
19	-4.0	98	2.28	XX
20	-2.0	154	3.58	XXXX
21	0.0	311	7.23	XXXXXXXX
22	2.0	2073	48.19	XX
23	4.0	331	7.69	XXXXXXX
24	6.0	283	6.58	XXXXXXX
25	8.0	275	6.39	XXXXXX
26	10.0	252	5.86	XXXXXX
27	12.0	190	4.42	XXXX
28	14.0	99	2.30	XX
29	16.0	35	0.81	X
30	18.0	8	0.19	
31	20.0	6	0.14	
32	22.0	0	0.00	
33	24.0	0	0.00	
34	26.0	0	0.00	
35	28.0	0	0.00	
36	30.0	0	0.00	
37	32.0	0	0.00	
38	34.0	0	0.00	
39	36.0	0	0.00	
40	38.0	0	0.00	
41	40.0	0	0.00	
42	>40.0	0	0.00	

FIGURE 3.21

V25 TEMPERATURE

NO. OF POINTS = 4302 BIN SIZE = .1 DEG C

BIN	BOUND	FREQ	PERCENT	
1	<12.0	0	0.00	
2	12.1	0	0.00	
3	12.2	0	0.00	
4	12.3	0	0.00	
5	12.4	0	0.00	
6	12.5	0	0.00	
7	12.6	0	0.00	
8	12.7	0	0.00	
9	12.8	0	0.00	
10	12.9	0	0.00	
11	13.0	27	0.63	X
12	13.1	20	0.46	
13	13.2	21	0.49	
14	13.3	26	0.60	X
15	13.4	69	1.60	XX
16	13.5	144	3.35	XXX
17	13.6	258	6.00	XXXXXX
18	13.7	338	7.86	XXXXXXXX
19	13.8	557	12.95	XXXXXXXXXXXX
20	13.9	591	13.74	XXXXXXXXXXXXXX
21	14.0	615	14.30	XXXXXXXXXXXXXX
22	14.1	526	12.23	XXXXXXXXXXXX
23	14.2	447	10.39	XXXXXXXXXXX
24	14.3	292	6.79	XXXXXXX
25	14.4	158	3.67	XXXX
26	14.5	104	2.42	XX
27	14.6	59	1.37	X
28	14.7	37	0.86	X
29	14.8	11	0.26	
30	14.9	2	0.05	
31	15.0	0	0.00	
32	15.1	0	0.00	
33	15.2	0	0.00	
34	15.3	0	0.00	
35	15.4	0	0.00	
36	15.5	0	0.00	
37	15.6	0	0.00	
38	15.7	0	0.00	
39	15.8	0	0.00	
40	15.9	0	0.00	
41	16.0	0	0.00	
42	>16.0	0	0.00	

FIGURE 3.22

V26 EAST

NO. OF POINTS - 4303 BIN SIZE - 2.0 CM/SEC

BIN	BOUND	FREQ	PERCENT	
1	<-40.0	0	0.00	
2	-38.0	0	0.00	
3	-36.0	0	0.00	
4	-34.0	0	0.00	
5	-32.0	0	0.00	
6	-30.0	0	0.00	
7	-28.0	0	0.00	
8	-26.0	6	0.14	
9	-24.0	8	0.19	
10	-22.0	13	0.30	
11	-20.0	24	0.56	X
12	-18.0	43	1.00	X
13	-16.0	97	2.25	XX
14	-14.0	101	2.35	XX
15	-12.0	179	4.16	XXXX
16	-10.0	338	7.85	XXXXXXXX
17	-8.0	340	7.90	XXXXXXXX
18	-6.0	428	9.95	XXXXXXXXXX
19	-4.0	429	9.97	XXXXXXXXXXX
20	-2.0	335	7.79	XXXXXXXX
21	0.0	260	6.04	XXXXXX
22	2.0	295	6.86	XXXXXXX
23	4.0	312	7.25	XXXXXXX
24	6.0	272	6.32	XXXXXX
25	8.0	258	6.00	XXXXXX
26	10.0	216	5.02	XXXXX
27	12.0	131	3.04	XXX
28	14.0	107	2.49	XX
29	16.0	61	1.42	X
30	18.0	32	0.74	X
31	20.0	16	0.37	
32	22.0	2	0.05	
33	24.0	0	0.00	
34	26.0	0	0.00	
35	28.0	0	0.00	
36	30.0	0	0.00	
37	32.0	0	0.00	
38	34.0	0	0.00	
39	36.0	0	0.00	
40	38.0	0	0.00	
41	40.0	0	0.00	
42	>40.0	0	0.00	

FIGURE 3.23

V26 NORTH

NO. OF POINTS = 4303 BIN SIZE = 2.0 CM/SEC

BIN	BOUND	FREQ	PERCENT	
1	<-40.0	0	0.00	
2	-38.0	0	0.00	
3	-36.0	0	0.00	
4	-34.0	0	0.00	
5	-32.0	0	0.00	
6	-30.0	0	0.00	
7	-28.0	0	0.00	
8	-26.0	0	0.00	
9	-24.0	0	0.00	
10	-22.0	0	0.00	
11	-20.0	0	0.00	
12	-18.0	0	0.00	
13	-16.0	0	0.00	
14	-14.0	0	0.00	
15	-12.0	0	0.00	
16	-10.0	5	0.12	
17	-8.0	15	0.35	
18	-6.0	65	1.51	XX
19	-4.0	234	5.44	XXXXX
20	-2.0	674	15.66	XXXXXXXXXXXXXXXXXXXX
21	0.0	1097	25.49	XXXXXXXXXXXXXXXXXXXXXXXXX
22	2.0	844	19.61	XXXXXXXXXXXXXXXXXXXXXX
23	4.0	506	11.76	XXXXXXXXXXXXXX
24	6.0	274	6.37	XXXXXX
25	8.0	141	3.28	XXX
26	10.0	96	2.23	XX
27	12.0	77	1.79	XX
28	14.0	62	1.44	X
29	16.0	45	1.05	X
30	18.0	45	1.05	X
31	20.0	32	0.74	X
32	22.0	42	0.98	X
33	24.0	18	0.42	
34	26.0	16	0.37	
35	28.0	8	0.19	
36	30.0	3	0.07	
37	32.0	3	0.07	
38	34.0	1	0.02	
39	36.0	0	0.00	
40	38.0	0	0.00	
41	40.0	0	0.00	
42	>40.0	0	0.00	

FIGURE 3.24

V26 TEMPERATURE

NO. OF POINTS = 4303 BIN SIZE = .1 DEG C

BIN	BOUND	FREQ	PERCENT
1	<9.0	0	0.00
2	9.1	0	0.00
3	9.2	0	0.00
4	9.3	0	0.00
5	9.4	0	0.00
6	9.5	0	0.00
7	9.6	0	0.00
8	9.7	0	0.00
9	9.8	1	0.02
10	9.9	3	0.07
11	10.0	17	0.40
12	10.1	18	0.42
13	10.2	21	0.49
14	10.3	44	1.02 X
15	10.4	96	2.23 XX
16	10.5	99	2.30 XX
17	10.6	99	2.30 XX
18	10.7	126	2.93 XXX
19	10.8	132	3.07 XXX
20	10.9	241	5.60 XXXXX
21	11.0	229	5.32 XXXXX
22	11.1	236	5.48 XXXXX
23	11.2	250	5.81 XXXXX
24	11.3	312	7.25 XXXXXX
25	11.4	326	7.58 XXXXXXX
26	11.5	333	7.74 XXXXXXX
27	11.6	477	11.09 XXXXXXXXXXX
28	11.7	286	6.65 XXXXXX
29	11.8	218	5.07 XXXXX
30	11.9	195	4.53 XXXXX
31	12.0	202	4.69 XXXXX
32	12.1	114	2.65 XXX
33	12.2	58	1.35 X
34	12.3	62	1.44 X
35	12.4	51	1.19 X
36	12.5	25	0.58 X
37	12.6	12	0.28
38	12.7	12	0.28
39	12.8	5	0.12
40	12.9	3	0.07
41	13.0	0	0.00
42	>13.0	0	0.00

FIGURE 3.25




FIGURE 3.26




FIGURE 3.27




FIGURE 3.28




FIGURE 3.29




FIGURE 3.30




FIGURE 3.31





FIGURE 3.32



4. Hourly Time Series

The raw velocity component and temperature data were truncated by the window of 2330 GMT 12 April 1987 to 1330 GMT 27 April 1987 to account for differences in the deployment and recovery times of the two moorings. The hourly vector averaged velocity components and scalar averaged temperature time series are shown in Figure 4 on page 43.

Figure 4. Figures 4.1 - 4.8: Hourly vector averaged time series of the velocity components and temperature.

FIGURE 4.1




FIGURE 4.2




FIGURE 4.3




FIGURE 4.4




FIGURE 4.5




FIGURE 4.6




FIGURE 4.7





FIGURE 4.8



5. Low Pass Filtered Time Series

The raw data were truncated as before to account for differences in the deployment and recovery of the moorings and for the filtering scheme. The records therefore begin at 2330 GMT 12 April 1987 and end at 1130 27 April 1987. The data were then low pass filtered using a ten percent cosine taper function with a six-hour sampling period and the resultant values were divided by .86 to correct for the reduction in magnitude caused by the filter. A cubic spline was applied to the filtered data as shown in Figure 5 on page 53.

Figure 5. Figures 5.1 - 5.8: Time series of the low pass filtered velocity components and temperature.

FIGURE 5.1




FIGURE 5.2




FIGURE 5.3




FIGURE 5.4




FIGURE 5.5




FIGURE 5.6




FIGURE 5.7





FIGURE 5.8



6. Low Pass Filtered Mooring Composites

The low pass filtered velocity component and temperature time series presented in section 5 are composited separately in Figure 6 on page 63 for moorings 87V1 and 87V2.

Figure 6. Figures 6.1 - 6.3: Low pass filtered velocity components and temperature time series composited for mooring 87V1. Figures 6.4 - 6.6: Same time series composited for mooring 87V2.

FIGURE 6.1
87V1 COMPOSITE
 U (Cm/Sec)




FIGURE 6.2
87V1 COMPOSITE
V (Cm/Sec)




FIGURE 6.3

87V1 COMPOSITE
Temperature (Deg C)




FIGURE 6.4

87V2 COMPOSITE
U (Cm/Sec)




FIGURE 6.5

87V2 COMPOSITE
V (Cm/Sec)





FIGURE 6.6

87V2 COMPOSITE
Temperature (Deg C)



7. Variance Density Spectra

The velocity and temperature variance spectra for the time series presented in section 3 are given in Figure 7 on page 72. The data were first truncated to the time window of 2330 12 April 1987 to 1330 27 April 1987 and were then broken up into seven 50-hour windows. The time series for each 50-hour window was demeaned and multiplied by a ten percent cosine taper function. The cosine tapered windows were then transformed using the FFTRC International Statistics and Mathematics Library (IMSL) routine. The variances from the 7 windows were then summed to increase the degrees of freedom to 14, and the sums were divided by 0.86 to correct for tapering. To decrease the noise in the higher frequency ranges, independent block averages of three band intervals were applied in the range from 0.5 C.P.H. (cycles per hour) to 2.0 C.P.H. for 42 degrees of freedom. Similarly, independent block averages of five band intervals were applied in the range from 2.02 C.P.H. to 6.0 C.P.H. for 70 degrees of freedom. The variances for the data are shown in Table 4 on page 71. The 90% confidence intervals for random errors were calculated based upon the chi-squared distribution with the given degrees of freedom and are shown in the figures.

Current Meter	East (Cm/Sec) ²	North (Cm/Sec) ²	Temperature (Deg C) ²
V11	79.14	29.05	25.19
V12	47.51	31.06	18.44
V13	48.18	35.56	16.77
v14	67.47	43.61	15.05
v15	70.24	45.17	14.36
v23	37.97	24.18	16.50
v25	50.81	21.91	14.91
v26	69.83	32.65	9.98

Table 4. Variances of the velocity components and temperature

Figure 7. Figures 7.1 - 7.8: Velocity component and temperature variance density spectra.

FIGURE 7.1

V11




FIGURE 7.2

V12




FIGURE 7.3

V13




FIGURE 7.4

V14




FIGURE 7.5

V15




FIGURE 7.6

V23




FIGURE 7.7

V25





FIGURE 7.8

V26



INITIAL DISTRIBUTION LIST

	No. Copies
1. Superintendent Naval Postgraduate School Attn: Professor R. W. Garwood, Jr., Code 68Gd Ms. S. Raugust, Code 68Ra Dr. P. C. Chu, Code 68Cu Chairman, Department of Oceanography, Code 68Co Library, Code 0142 Research Administration, Code 012 Monterey, CA 93943-5000	20 4 1 1 2 1
2. Defense Technical Information Center Cameron Station Alexandria, VA 22304-6145	2
3. Chief of Naval Research Attn: Dr. M. G. Briscoe, Code 422PO Dr. A. Bucklin 800 N. Quincy Street Arlington, VA 22217	1 1 1
4. Commander Naval Oceanographic Office Attn: Library, Code 3330 Washington, D. C. 20373	1
5. Commanding Officer Naval Underwater Systems Center Newport, RI 02840	1
6. Officer-in-Charge New London Laboratory Naval Underwater Systems Center New London, CT 06320	1
7. Director Advanced Research Project Agency 1400 Wilson Boulevard Arlington, VA 22209	1
8. Director of Defense Research and Engineering Office of Assistant Director (Ocean Control) The Pentagon Washington, D. C. 20301	1
9. Commander Naval Sea Systems Command Department of the Navy Washington, D. C. 20362	1
10. Commanding Officer Naval Coastal Systems Laboratory Panama City, FL 32401	1

11. Commander
Space and Naval Warfare Systems Command
Department of the Navy
Washington, D. C. 20360
12. Director
Marine Physical Laboratory
Scripps Institution of Oceanography
San Diego, CA 92132
13. Scientific Liaison Office
Office of Naval Research
Scripps Institution of Oceanography
La Jolla, CA 92037
14. Scripps Institution of Oceanography
Attn: Library
P. O. Box 2367
La Jolla, CA 92037
15. School of Oceanography
University of Washington
Attn: Library
Dr. M. Gregg
Dr. C. Eriksen
Seattle, WA 98195
16. School of Oceanography
Oregon State University
Attn: Library
Corvallis, OR 97331
17. Chairman
Department of Oceanography
U. S. Naval Academy
Annapolis, MD 21402
18. Department of Ocean Engineering
Attn: Library
Massachusetts Institute of Technology
Cambridge, MA 02139
19. Commander
Naval Oceanography Command
NSTL Station
Bay St. Louis, MS 39529
20. Commanding Officer
Fleet Numerical Oceanography Center
Monterey, CA 93943
21. Commanding Officer
Naval Environmental Prediction Research Facility
Monterey, CA 93943

22. Commanding Officer
Naval Ocean Research and Development Activity
Attn: Technical Director
NSTL Station
Bay St. Louis, MS 39522 1
23. Director
Naval Oceanography Division
Naval Observatory
34th and Massachusetts Avenue NW
Washington, D. C. 20390 1
24. Director
Woods Hole Oceanographic Institution
Attn: Dr. K. Brink
Library
Woods Hole, MA 02543 1
25. Director
Naval Research Laboratory
Attn: Technical Information Division
Washington, D. C. 20375 1
26. Institute of Ocean Sciences
Attn: Dr. G. Holloway
P. O. Box 6000 1
Sidney, British Columbia
Canada
V8L 4B2
27. Commander
Naval Weapons Center
Attn: Library
China Lake, CA 93555 1
28. Commander Submarine Force
U. S. Pacific Fleet
Pearl Harbor, HI 96860-65550 1
29. Commander Submarine Force
U. S. Atlantic Fleet
Norfolk, VA 23511 1
30. Director, Honolulu Laboratory
Attn: Dr. G. Boehlert
Mr. C. Wilson
National Marine Fisheries Service, NOAA
P. O. Box 3830
Honolulu, HI 96812 8
1
31. Director, Pacific Marine Environmental Laboratory
Attn: Dr. J. Schumacher
NOAA
7600 Sand Point Way NE
Seattle, WA 98115-0070 1

32. Director, Atlantic Oceanographic and Meteorological Laboratories
Attn: Dr. D. Hansen 1
NOAA
4301 Rickenbacker Causeway
Miami, FL 33149
33. Commanding Officer
NOAA Ship TOWNSEND CROMWELL
Attn: I T R. Brainard 4
#1 Sand Island Access Road
Honolulu, HI 96819
34. U. S. Geological Survey
Attn: Dr. M. Noble 1
345 Middlefield Road
MSS 999
Menlo Park, CA 95025